

TRASYS OVERVIEW

TRASYS Is A General-Purpose Thermal Radiation Analysis System Computer Code Capable Of Producing:

- INTERNODE RADIATION INTERCHANGE FACTORS**
- INCIDENT & ABSORBED ENVIRONMENTAL HEAT LOADS**

TRASYS RESULTS MAY BE USED IN CONJUNCTION WITH ANY THERMAL ANALYZER CODE, SUCH AS AC/SINDA FOR TEMPERATURE PREDICTIONS.

TRASYS CAPABILITIES

- **2000 NODES**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**
- **USER-DEFINED CONSTANTS**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**
- **USER-DEFINED CONSTANTS**
- **RESTART CAPABILITY**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**
- **USER-DEFINED CONSTANTS**
- **RESTART CAPABILITY**
- **VARIABLE GEOMETRY OPTION**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**
- **USER-DEFINED CONSTANTS**
- **RESTART CAPABILITY**
- **VARIABLE GEOMETRY OPTION**
- **CHOICE OF SOLUTION TECHNIQUES FOR VF**

TRASYS CAPABILITIES

- **2000 NODES**
- **13 SURFACE TYPES**
- **SHADOWING OF INTERVENING SURFACES**
- **OPAQUE or SEMITRANSSPARENT SURFACES**
- **EXTERNALLY-SUPPLIED VIEW FACTORS**
- **USER-DEFINED ACCURACY PARAMETERS**
- **USER-DEFINED SPECIFIC ROUTINES**
- **USER-DEFINED CONSTANTS**
- **RESTART CAPABILITY**
- **VARIABLE GEOMETRY OPTION**
- **CHOICE OF SOLUTION TECHNIQUES FOR VF**
- **CONTAMINATION ANALYSIS INTERFACE**

A TYPICAL THERMAL ANALYSIS PROCEDURE

