

# TIMEWISE

32 Old Barn Road  
Hawthorn Woods, Illinois 60047 USA  
(847) 550-5052

## PRICE LIST, DOMESTIC\*

Effective October 29, 2008

MODEL	DESCRIPTION	PRICE
798A	Professional Rally Computer (incl. Model 398 Driver's Display) .....	\$1375.00
747A	Rally Computer designed for the Pony Express™ and Silver State Classic™ .....	730.00
547B	Rally Odometer (Overall and Trip), Timer, & Clock; with 250 split memory .....	595.00
825	Analog Reading Electronic Speedometer; .0125 mph accuracy; 4.5" diameter .....	990.00
660	Multi-split/Multi-Function Checkpoint Timer/Clock; with 75 split memory .....	285.00
397-3	Driver's Display for discontinued Models 797A and 796A; 3 ft cable .....	195.00
398-3	Driver's Display for Model 798A (replacement); 3 ft cable .....	250.00
326-3	Driver's Display for Models 547B, 747A, & discontinued 526B; 3 ft cable .....	230.00

### OPTIONS

Note: Some options alter standard features. Consult TIMEWISE for details.

798A/1	Datalog of last 56 CASTs and Splits; for 798A .....	50.00
798A/2	Automatic reverse (off-course) when backing up (cable not included); for 798A .....	75.00
798A/3	Adds Timer; simultaneous Error, Odo and Timer reset, splittable Error; for 798A .....	37.50
798A/4	RS-232C interface; for 798A .....	30.00
798A/5	Include ability to adjust the auxiliary odometer; for 798A .....	15.00
798A/6	Allows setting CASTs with .01 mph resolution; for 798A .....	15.00
798A/7	Add ability to remotely select alternate parameter in driver's auxiliary display; for 798A .....	50.00
798A/8	Rear panel BNC with 1 Hertz synchronization signal; for 798A .....	75.00
798A/9	Adjustable ERROR offset bias (-0.9 to +0.9); for 798A (add \$50 if not ordered with original purchase)...	85.00
798A/10	Discretionary "Intelli-Fix" ORM correction during a LAST CAST adjustment; for 798A .....	15.00
798A/11	Automatic CAST execution at a preset distance; for 798A .....	15.00
798A/12	"Locking" FWD-PARK-REV toggle switch (if ordered with original purchase); for 798A .....	15.00
547B/1	Battery backed Real Time Clock (RTC); for 547B .....	20.00
547B/2	Built-in odometer input pulse divider (÷1, ÷2, ÷4, ÷8, ÷16); for 547B .....	27.00
547B/3	RS-232C printer output of Clock when Split activated; for 547B .....	37.50
547B/4	Remote Recall input connector installed; for 547B .....	37.50
650/1	6 - 9 volt DC input power jack allowing continuous backlighting of LCD display; for 650 .....	15.00
650/2	RS232-C Interface; for 650 .....	37.50

Options for discontinued Models 526B, 610, 650, and 797A are also available. Call for details.

### ODOMETER INPUT SENSORS

345-DB	NRS Hub Drive system, w/ 215.0-7M-SR sensor, 450 coupler, 111-10 cable, PC2.5/8 mag. holder .....	655.00
217-15	Super-sensitive Permalloy sensor (to sense magnets); 8 contact modular plug; 15 ft .....	59.50
215.0-7	Speedometer cable sensor; 5/8" x 18 fittings; .105" square key; 8 cont. modular plug; 7 ft .....	82.00
215.0-7M	Speedometer cable sensor; 5/8" x 18 male; closed other end; .125" sq. key; 8 cont. modular plug; 7 ft .....	87.00
215.1-7	Speedometer cable sensor; 7/8" x 18 fittings; .105" square key; 8 cont. modular plug; 7 ft .....	86.00
215.2-7	Speedo cable sensor; 5/8" x 18 male; 7/8" x 18 female; .105" sq. key; 8 cont. mod. plug; 7 ft .....	86.00
445	5/8" x 18 to 7/8" x 18 reducer/enlarger for speedometer cable sensor .....	8.75
215.3-7	Speedo cable sensor; 18mm x 1.5mm fittings; .105" square key; 8 contact mod. plug; 7 ft .....	100.00
215.4-7	Speedo cable sensor; adaptable key size†; 22mm x 1.5mm fittings; 8 contact mod. plug; 7 ft .....	100.00
215.5-7	Speedo cable sensor; adaptable key size†; 7/8" x 18 fittings; 8 contact modular plug; 7 ft .....	94.00
-x	Additional cable length (replace -x with total length in feet) .....	per additional foot, add 1.55
-pull-up	Internal pull-up resistor on sensor output signal (1K ohm unless specified otherwise) .....	add 2.25
-seal	Silicone rubber coating to waterproof speedometer cable sensor .....	add 6.00
-SR	Strain relief installed on speedometer cable sensor wiring; required with NRS Hub Drive .....	25.00
	Replace modular plug w/ CINCH P-303-CCT plug or SWITCHCRAFT SL-403M plug .....	add 2.25
	Delete modular plug .....	subtract 3.75

† Requires one each of a male and female drive key. Specify either .105", .125", .150", or .187" square key or .152", .187", or .203" tang key. See accessories for part number and cost. Contact TIMEWISE for adapters to other types and sizes of speedometer cable fittings and keys.

\* Prices do not include shipping.

## TIMEWISE domestic price list\*, continued

Effective October 29, 2008

### ODOMETER INPUT SENSOR ADAPTERS & EXTENSION CABLES

<b>110-1</b>	8 contact modular plug to "no connector" (cable blunt cut, then stripped and tined); 1 ft .....	5.30
<b>111-1</b>	8 contact modular plug to 8 contact modular plug; 1 ft .....	9.05
<b>112-1</b>	8 contact modular plug to SWITCHCRAFT SL-413F socket; 1 ft .....	11.30
<b>113-1</b>	8 contact modular plug to CINCH S-303-CCT socket; 1 ft .....	11.30
<b>123-1</b>	SWITCHCRAFT SL-403M plug to CINCH S-303-CCT socket; 1 ft .....	13.25
<b>-x</b>	Additional cable length (replace -x with total length in feet) .....	per additional foot, add 1.55
	Replace modular plug w/ CINCH P-303-CCT plug or SWITCHCRAFT SL-403M plug .....	add 2.25
	Delete modular plug .....	subtract 3.75

### ACCESSORIES & SUPPLIES

<b>405</b>	Mounting bracket for Model 217 sensor (6" x 0.75" x 0.15"); zinc plated steel .....	3.00
<b>406</b>	Mounting bracket for Model 217 sensor (8" x 1.00" x 0.15"); tin plated copper .....	3.00
<b>410</b>	Magnets for Model 217 sensor; ceramic; 0.5" dia x 0.2"; pkg. of 5; (from Radio Shack) .....	5.75
<b>410-2</b>	Magnets for Model 217 sensor; ceramic; 7/8" x 1/4" x 5/16"; each; red dot on South pole .....	1.00
<b>415</b>	Replacement Ni-Cad battery (8.4 volt) for discontinued Model 526B .....	22.50
<b>420-xxx</b>	Instrument mounting bracket (replacement), specify model (-xxx indicates model) .....	18.00
<b>425</b>	Plastic mounting knob for instrument mounting brackets (replacement) .....	3.50
<b>430</b>	Hard rubber washer for instrument mounting brackets (replacement) .....	0.75
<b>431</b>	Transducer hex nuts; Nickel plated steel, 1/8" IPS NPT x 5/8" across flats x 3/16" thick .....	1.00
<b>432</b>	Transducer lockwasher; 3/8" inside toothed, zinc plated steel .....	0.10
<b>435</b>	.105" square drive key for Model 215.0/1/2/3 sensor (replacement) .....	8.00
<b>436-xxx</b>	Male square drive key for Model 215.4/5 sensors‡ (-xxx indicates square pin size) .....	10.00
<b>437-xxx</b>	Female square drive key for Model 215.4/5 sensors‡ (-xxx indicates square hole size) .....	12.00
<b>436-xxxT</b>	Male tang drive key for Model 215.4/5 sensors‡ (-xxx indicates tang diameter size) .....	12.00
<b>437-xxxT</b>	Female tang drive key for Model 215.4/5 sensors‡ (-xxx indicates tang hole size) .....	14.00
<b>440</b>	Odometer Input Jumper Plug (replacement) .....	3.75
<b>445</b>	5/8" x 18 to 7/8" x 18 reducer/enlarger for Model 215.2 speedometer cable sensor .....	8.75
<b>450</b>	In-line modular jack coupler to connect two 8 contact RJ45 modular plugs straight through .....	7.50
<b>455</b>	Dust Cover Plug for unused 8 contact modular jacks (replacement on 547B) .....	1.50
<b>460-xxx</b>	Handheld pendant switch, heavy duty; w/ 6 ft cable & 1/8" stereo plug;(specify application) .....	52.50
<b>461-xxx</b>	Handheld pendant switch, light duty; w/ 4 ft cable & 1/8" stereo plug;(specify application) .....	29.50
<b>465</b>	Replacement DC Power Cord with Fuse Holder, includes 2 Amp Fuse .....	15.00
<b>470</b>	Right angle 1/8" stereo plug adapter .....	7.50
<b>475</b>	Right angle 1/8" stereo plug for remote control input .....	4.00
<b>480</b>	Clock synchronization cable, 1/8" stereo plug each end, 6 feet long .....	10.00
<b>485</b>	Epoxy for magnets .....	5.50
<b>PC2.5/8</b>	PrecisionCraft magnetic mount electrical cable holder for use with HRS Hub Drive (replacement) .....	45.00
<b>1001-x</b>	User's Manual (replacement), specify model (-x indicates model) .....	10.00

‡ specify: .105", .125", .150", or .187" square key or .152", .187", or .203" tang key

Contact TIMEWISE for adapters to other types and sizes of speedometer cable fittings and keys.

\* Prices do not include shipping.